ANCHORS AND SEALANTS

METAL ANCHORS

Cealing cavity fixings

APPLICATION

Used to fix items to the ceiling or on empty walls.

FEATURES AND BENEFITS

AS8

- > Provided with spring or rocker arm to guarantee a solid and fast installation.
- > They can be used on walls with different thicknesses ensuring great flexibility as well.



DD10





COD	ТҮРЕ	Hole Ø mm	Min. drilling depth (mm)	Max. fixable thickness (mm)	A	E	G
131210	OC 6	16	65	30	60	-	14
131230	DD 6	16	65	30	60	M6	-
131235	AS 8	20	65	35	60	M8	-
131240	DD 8	20	75	35	70	M8	
131250	DD 10	22	90	35	85	M10	



ANCHORS AND SEALANTS

METAL ANCHORS

MATERIALS TECHNICAL DATA

ANCHOR

Steel 4.8 EN ISO 898-1 with electro zinc plating 7-8 µm

BASE MATERIAL

Hollow brick walls

RECOMMENDED LOADS



Recommended load is the average resistance loads with a safety coefficient.

Data expressed in daN. 1daN=1kg.

N.B.: the kind of support may affect the anchoring's resistance. Chart's values refer to the maximum resistance of the product, therefore it is recommended to use a proper safety coefficient, according to the support's base material.

INSTALLATION TOOLS AND RECOMMENDATIONS

Drill with a proper drill bit.

PACKAGING

In cardboard box

DATE 06-2023 REV. 02

The current technical data sheet substitutes and cancels the previous ones. The details provided fit our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation. Gia S.p.A. reserves the right of changing technical features and molds without notice. This company is subject to "Ethica Global Investments S.p.A." management.

Gia S.p.A. - Via Sac. A. Cremona, 12 - 28069 Trecate (NO) - www.gia.it

