
Heavy duty pipe clamp with AF/ARMAFLEX insulated sleeve

APPLICATION


Suitable for fixing and heat insulation of heating, air-conditioning and refrigeration systems.

FEATURES AND BENEFITS

- > The **perfect closure** of the insulation material and its **uniformity** with the rest of the insulation prevents condensation and ensures **maximum reduction of heat loss.**
- > Insulation quality is ensured by the **Armacell AF/ARMAFLEX sleeve.**
- > The heavy duty pipe clamp is made of galvanized steel and completed with an electro-welded nut and locking screws with red washers and an AF/ARMAFLEX Armacell sleeve.







COD	TYPE	For pipe lines Ø mm	Max supports distance (mt)	Α	В	С	D	E	F	н	L	Notes
086000	STO1P 1/4"	10-14	2,00	3	20	72	M8	M6x20	54	45	13	
086010	STO1P 3/8"	15-18	2,25	3	20	81	M8	M6x20	58	45	13	
086020	STO1P 1/2"	20-25	2,75	3	20	88	M8	M6x20	67	45	13	
086030	STO1P 3/4"	26-28	3,00	3	20	93	M8	M6x20	71	45	13	
086040	STO1P 1"	32-35	3,50	3	20	98	M8	M6x20	80	50	13	
086050	STO1P 1 1/4"	40-43	3,75	3	30	117	M10	M6x20	89	50	13	
086060	STO1P 1 1/2"	48-50	4,25	3	30	126	M10	M6x20	95	55	13	
086070	STO1P 2"	59-62	4,72	3	30	137	M10	M6x20	112	65	13	
086080	STO1P 2 1/2"	75-78	5,50	3	30	181	M10	M6x20	145	85	19	
086090	STO1P 3"	88-90	6,00	4	40	218	F.1/2"-F.M12	M8x35	160	100	19	*
086100	STO1P 4"	112-114	6,00	4	40	247	F.1/2"-F.M12	M8x35	180	115	19	*

^{*} Flat head locking screws without red washer and locking nut.





MATERIAL TECHNICAL DATA

MATERIAL

Steel DD11 (material. N. 1.0332) DIN EN 10111

GALVANIZATION

Electro zinc-plating 7-8 µm

CONNECTING THREAD

M8 or M10

LOCKING SCREW

Steel 4.8 EN ISO 898.1 with electro zinc-plating 7-8 µm

M6x20 - Hex head combined shear screw

M8x35 - Hex head flat shear screw

INSULATING SHEATH

Armafix AF

RIGID SEGMENTS' DENSITY

145 kg/m³

TEMPERATURE

- 50°C / + 105°C

CONDUCTIVITY

 \leq 0,040 W/mk a 40°C - for AF-5/AF-6 pipe line

RESISTENCE FACTOR TOG AS SPREAD

 $\mu \ge 7000$ - for AF-5/AF-6 pipe line

PERFORMANCE UNDER FIRE SITUATIONS

DIN 4102-B2

PACKAGING

In plastic bag I 1 piece

DATE 03-2019 REV. 00

The current technical data sheet substitutes and cancels the previous ones. Information correspond with our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation. Gia S.p.A. reserves the right of changing techical features and molds without notice.

Gia S.p.A. - Via Sac. A. Cremona, 12 - 28069 Trecate (NO) - www.gia.it

