



## G-ATTACK CRISTALLO

### Crystal hybrid adhesive sealant

#### APPLICATION

It is used to seal and stick together a wide range of supports and materials.

#### FEATURES AND BENEFITS

- > **Silane terminated hybrid polymer** which hardens when in contact with air humidity.
- > **Free** from isocyanates and solvents.
- > Anti-mould (compliant with ISO 846 regulation).
- > **Permanent elasticity.**
- > High **exterior hardness.**
- > **Odorless.**
- > Excellent **transparency**, with great **chromatic stability.**
- > **Long lasting** adhesive properties.
- > **It can be painted.**
- > **No primer** needed for adhesion.
- > **Excellent extrusion.**
- > **Resistant to UV rays.**

#### Recommended on:

- Glass
- Mirrors
- Porcelain and ceramic
- Wood and cork
- Brick, concrete
- Aluminium, painted aluminium
- Steel, stainless steel
- Iron, lead
- PVC, PC

Avoid permanent contact with water and fish tankers.



COD	TYPE	Description	Cartridge capacity	Storage life
155285	G-ATTACK CR	Crystal	300 ml	14 months



**MATERIALS TECHNICAL DATA****MATERIAL**

Silane terminated hybrid polymer sealant.

**STORAGE TEMPERATURE**

+ 5°C / + 25°C

When stored in its original package - in a fresh and dry environment, and protected from light exposure - the product lasts 24 months.

**PREPARATION AND USAGE****USAGE CONDITIONS**

Use the product at a temperature included within + 5°C and + 50°C. In order to guarantee the best performance, it is suggested to use it at a temperature of about 20°C.

Let the product dry completely before painting it.

**SURFACE REQUIREMENTS**

The surface where the product is to be applied on must be dry, free from dust, oil, and grease.

Once the surface is clean, apply the product within - and not later than - 20 minutes.

**INSTALLATION TOOLS AND CLEANING**

Both manual and pneumatic guns may be used for product extrusion. After use, clean the tools with mineral spirits. Whether there are spots or residual material left, use mineral spirits to remove those parts which are not dry yet, while the other ones - that are already hardened - can be removed only mechanically.

**PACKAGING**

In cardboard box | 12 items

**RELATED ITEMS**

> G-ATTACK BIANCO - White hybrid adhesive sealant

**DATA 09-2020 REV. 00**

The current technical data sheet substitutes and cancels the previous ones. Information correspond with our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation.

Gia S.p.A. reserves the right of changing technical features and molds without notice.

**Gia S.p.A. – Via Sac. A. Cremona, 12 – 28069 Trecate (NO) – [www.gia.it](http://www.gia.it)**

T 05.27A.135E REV 0

