

G-ATTACK CRISTALLO

High performing crystal adhesive sealant

APPLICATION

Suitable to seal and stick a wide range of supports and materials. In case of applications in which high load capacity is required, it is recommended to use G-ATTACK BIANCO.


FEATURES AND BENEFITS

- > **One-component adhesive sealant**, suitable for a wide range of applications. High performing product with **permanent elasticity**.
- > **Ready for use**.
- > **Very good extrusion**.
- > **Free** from solvents, phthalates, isocyanates.
- > Remarkable **superficial hardness**.
- > **Odorless**.
- > Excellent **transparency**, with great **color stability**.
- > Its adhesive properties **keep unchanged in time**.
- > **It can be painted**.
- > It works **both on dry and wet surfaces**.
- > It works **underwater as well**.
- > **It is certified for food usage**.




Recommended on:

- Glass
- Mirrors
- Porcelain and ceramic
- Wood and cork
- Brick, concrete
- Aluminum, painted aluminum
- Steel, stainless steel
- Iron, lead
- PVC, PC



1935/2004 CE Regulation
when in contact with food



COD	TYPE	Description	Cartridge Capacity	Storage Life
155286	G-ATTACK CR	Crystal	290 ml	12 months

ANCHORS AND SEALANTS

SILICONE SEALANTS AND CHEMICAL ANCHORS

MATERIALS TECHNICAL DATA

MATERIAL

One-component sealant, made of MS polymer.

Danger warnings:

EUH210 Safety data sheet available on request.

EUH208 It contains:
TRIMETHOXYVINYLILANE
It can cause allergies.

STORAGE TEMPERATURES

+ 5°C / + 25°C

The product lasts 12 months when stored in its original packaging, in a dry and cool environment, safe from direct light exposure.

PREPARATION AND USAGE

USAGE CONDITIONS

Use the product at a temperature that is included within + 5°C and + 40°C. In order to guarantee the best performance, it is suggested to use it at a temperature of about 20°C.

Let the product dry completely before painting it.

When sealing mirrors in bathrooms, make sure to apply adhesive's vertical stripes only. Check whether the sealant has correctly stuck on PP, PE, BITUMEN and silicone sealants. When different varnishes have been applied on one another, the product might dry more slowly.

SURFACE REQUIREMENTS

The surface - on which the product is to be applied - must be dry, free from dust, oils, and grease. Once the surface is clean, apply the product within - and not later than - 20 minutes.

INSTALLATION TOOLS AND CLEANING

Both manual and pneumatic guns may be used for product extrusion. After use, clean the tools with mineral spirits. Whether there are spots or residual material left, use mineral spirits to remove those parts which are not dry yet, while the other ones - that are already hardened - can be removed only mechanically.

PACKAGING

In cardboard box - 12 pieces

RELATED ITEMS

> G-ATTACK BIANCO - High performing white adhesive sealant

DATE 06-2023 REV. 01

The current technical data sheet substitutes and cancels the previous ones. The details provided fit our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation.

Gia S.p.A. reserves the right of changing technical features and molds without notice.

This company is subject to "Ethica Global Investments S.p.A." management.

Gia S.p.A. – Via Sac. A. Cremona, 12 – 28069 Trecate (NO) – www.gia.it