



SIL-AT / SIL-AB

High performing anti-mould acetic silicone sealant

APPLICATION

Used for sanitary and pottery sealing.

FEATURES AND BENEFITS

- > **Acetic** silicone sealant with anti-mould additive.
- > Fast polymerization.
- > It is particularly suitable for sealings in areas where there is a high condensation and humidity level, such as **bathrooms, sanitary fixtures and general pottery.**
- > It guarantees **excellent adhesion** on nonporous surfaces such as ceramic, aluminium and vitreous surfaces.
- > Its formula ensures **U.V. rays resistance** and **long lasting elasticity.**

Not recommended on:

- Concrete
- Masonry
- Natural stone
- Metals (lead, copper, zinc, steel)
- Plastic, PE, PP and Teflon
- Membranes and bitumens
- Wood

Avoid permanent contact with water or fish tanks.

It cannot be painted.



COD	TYPE	Description	Cartridge capacity	Storage life
155200	SIL-AT	Acetic - transparent	280 ml	18 months
155220	SIL-AB	Acetic - white	280 ml	18 months



**MATERIALS TECHNICAL DATA****MATERIAL**

Acetic silicone sealant with anti-mould additive.

STORAGE TEMPERATURE

+ 5°C / + 25°C

PACKAGING

In cardboard box | 24 items

RELATED ITEMS

- > SIL-NT / SIL-NB - Anti-mould neutral silicone sealant
- > SIL-HT - High temperature silicone sealant
- > SIP - PE foam protection strip

DATA 09-2020 REV. 00

The current technical data sheet substitutes and cancels the previous ones. Information correspond with our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation. Gia S.p.A. reserves the right of changing technical features and molds without notice.

Gia S.p.A. – Via Sac. A. Cremona, 12 – 28069 Trecate (NO) – www.gia.it

T 05.27A.135A REV 0

