



## SIL-NT / SIL-NB

### High performing anti-mould neutral silicone sealant

#### APPLICATION

Professional sealings even in moist environments.

#### FEATURES AND BENEFITS

- > Neutral silicone sealant with alcoholic and anti-mould composition.
- > Fast polymerization and high elasticity.
- > It is particularly recommended to seal sanitary fixtures, showers, bathrooms, saunas and any other application in areas with high condensation and humidity levels, or whether it is required a high hygienic level.
- > It guarantees **excellent adhesion** on nonporous surfaces such as ceramic, aluminium and vitreous surfaces.
- > Suitable even for window fixtures, wood, iron and concrete.
- > Its formula ensures **resistance to U.V. rays** and **atmospheric agents**.

#### Not recommended on:

- Natural stone
- Membranes and bitumens
- PE, PP and Teflon

Avoid permanent contact with water or fish tanks.

It cannot be painted.



COD	TYPE	Description	Cartridge capacity	Storage life
155240	SIL-NT	Neutral - transparent	280 ml	15 months
155260	SIL-NB	Neutral - white	280 ml	15 months



## ANCHORS AND SEALANTS

### SILICONE SEALANTS

#### MATERIALS TECHNICAL DATA

##### MATERIAL

Neutral silicone sealant with alcoholic and anti-mould composition.

##### STORAGE TEMPERATURE

+ 5°C / + 25°C

##### PACKAGING

In cardboard box | 24 items

#### RELATED ITEMS

- > SIL-AT / SIL-AB - Anti-mould acetic silicone sealant
- > SIL-HT - High temperature silicone sealant
- > SIP - PE foam protection strip

#### DATA 09-2020 REV. 00

The current technical data sheet substitutes and cancels the previous ones. Information correspond with our current knowledge of the product. It cannot lead us to any sort of responsibility or compensation. Gia S.p.A. reserves the right of changing technical features and molds without notice.

Gia S.p.A. – Via Sac. A. Cremona, 12 – 28069 Trecate (NO) – [www.gia.it](http://www.gia.it)

T 05.27A.135B REV 0

